

Air Screwdrivers / Straight Models
Visseuses Pneumatiques / Modèles à Poignée Droite
Druckluft-Drehschrauber, gerade Ausführung
Atornilladores Neumáticos / Modelos con Empuñadura Recta
Cacciaviti Pneumatici / Modelli con Impugnatura Diritta



LD Series

Standard Equipment

Vertical hanger

Suspension verticale

Vertikal-Aufhänger


Suspensión vertical

Disp. sospensione verticale

Options


Ref. **DV7MB14FB14**

Variacor air hose universal joint
 Raccord tournant Variacor
 Lufteinlaß-Drehgelenk Variacor
 Conexión giratoria Variacor
 Raccordo girevole Variacor



Ref. **LDX2XXRDX-XX-DI**

Dual information kit ⁽¹⁾
 Kit prise d'info ⁽¹⁾
 2-fach Signal ⁽¹⁾
 Doble señal ⁽¹⁾
 Doppia informazione ⁽¹⁾



LD Series

Adjustable shut-off clutch models
 Modèles avec limiteur réglable à coupure d'air
 Modelle mit einstellbarer Abschaltkupplung
 Modelos con parada automática
 Modelli con frizione regolabile con blocco aria

Specifications at 90 psi – Caractéristiques à 620 kPa – Technische Daten bezogen auf 620 kPa – Especificaciones a 620 kPa – Caratteristiche a 620 kPa

Ref.	 Nm	 1 min. rpm	 kg	 mm	 mm	 in	 l/min
☞ LEVER START — DÉM. PAR LEVIER — HEBELSTART — ARRANQUE POR PALANCA — AVVIAMENTO A LEVA							
LD1214RD5-Q4	1.1 - 2.5	1500	0.7	231	17	1/4" ♂	460
LD1207RD5-Q4	1.2 - 4.2	800	0.7	231	17	1/4" ♂	460
LD2216RD5-Q4	1.8 - 4.5	1550	1.0	272	18	1/4" ♂	620
LD2210RD5-Q4	2.4 - 5.9	1000	1.0	272	18	1/4" ♂	620
LD2206RD5-Q4	2.1 - 9.8	600	1.0	272	18	1/4" ♂	620
LD1202RD5-Q4	1.6 - 10	180	0.8	243	17	1/4" ♂	460
LD2203RD5-S6	10 - 15	300	1.1	293	18	3/8" □	620
☞ LEVER + PUSH START — LEVIER + POUSÉE — HEBELSTART + SCHUBSTART — PALANCA + EMPUJE — LEVA + SPINTA							
LD1214RD1-Q4	1.1 - 2.5	1500	0.7	231	17	1/4" ♂	460
LD1207RD1-Q4	1.2 - 4.2	800	0.7	231	17	1/4" ♂	460
LD2216RD1-Q4	1.8 - 4.5	1550	1.0	272	18	1/4" ♂	620
LD2210RD1-Q4	2.4 - 5.9	1000	1.0	272	18	1/4" ♂	620
LD2206RD1-Q4	2.1 - 9.8	600	1.0	272	18	1/4" ♂	620
☞ PUSH START — DEM. PAR POUSÉE — SCHUBSTART — ARRANQUE POR EMPUJE — AVVIAMENTO A SPINTA							
LD1214RD3-Q4	1.1 - 2.5	1500	0.7	231	17	1/4" ♂	460
LD1207RD3-Q4	1.2 - 4.2	800	0.7	231	17	1/4" ♂	460
LD2216RD3-Q4	1.8 - 4.5	1550	1.0	272	18	1/4" ♂	620
LD2210RD3-Q4	2.4 - 5.9	1000	1.0	272	18	1/4" ♂	620
LD2206RD3-Q4	2.1 - 9.8	600	1.0	272	18	1/4" ♂	620
LD1202RD3-Q4	1.6 - 10	180	0.8	243	17	1/4" ♂	460

(1) For dual information kit, add "-DI" to tool model no. (e.g. LD2216RD5-Q4-DI).

(1) Pour kit prise d'info, ajouter "-DI" à la référence (exemple LD2216RD5-Q4-DI).

(1) 2-fach Signal: ergänzen Sie die Modell-Nr. mit "-DI" (z. B. LD2216RD5-Q4-DI).

(1) Para doble señal, añadir "-DI" a la referencia (ejemplo LD2216RD5-Q4-DI).

(1) Per doppia informazione, aggiungere "-DI" al codice del modello (es. LD2216RD5-Q4-DI).

Series / Baureihe			
LD12	70 dBa	1/4" BSP	9 mm
LD22	72 dBa	1/4" BSP	13 mm